

THERMAXX	THE ADVANTAGE IS TO YOUR BOTTOM LINE	
BODY DIMENSION External length External width External height	3300mm 2490mm 2000mm	Side door Rear door
Internal length Internal width Internal height	3140mm 2410mm 1800mm	Front wall f
Pallet loading	4 Pallet capacity	Rear step
Fitted body wei	ght *II55kg	Cargo track

J	
Pallet loading	4 Pallet capacity
Fitted body weight	*1155kg
PANELS THICKNESS Roof/floor Front wall Side walls/side doors Rear doors	100mm 100mm 40mm 60mm

Side door	Passenger side pallet door 1800 × 1400mm	
Rear door	Double - (left opens first)	
Front wall frame	Universal to suit off engine drive units	
Side step	Fixed rung step	
Rear step	Fixed plank step	
Cargo track	I recessed row @ 900mm I shoring bar	
Floor	One piece aluminium ricegrain	
Internal light	I LED sensor light	
Refrigeration	*Thermo King SV-400	

-20°C\*

13.62m<sup>3</sup>



## Thermal efficiency 'K' VALUE .57 W/m<sup>2</sup>K tested to Australian Standard AS4982

## **Standard Inclusions**

- High density polyurethane insulation
- European design
- European construction
- Low tare weight
- Higher legal payload
- sub frame

- Recessed stainless door hardware
- Stainless door frames
- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor light
- Rubber bump stops
- Model No: A3300P-BDEHI
  - Rear/side grab handlesMoulded plastic mudguards
  - Alloy kick panel
  - Options available to suit customer requirements



