

THERMAXX THE A	DVANTAGE IS TO YOUR
BODY DIMENSION External length External width External height	7800mm 2490mm 2650mm
Internal length Internal width Internal height	7620mm 2410mm 2450mm
Pallet loading	12 Pallet capacity
Fitted body weight	*2964kg
PANELS THICKNESS Roof/floor Front wall Side walls	100mm 100mm 40mm

Side door	N/A
Rear door	Double (left opens first)
Front wall frame	Universal to suit diesel drive units
Side step	N/A
Rear step	Heavy duty crash bar
Cargo track	2 recessed rows @ 800-1400mm 2 shoring bars
Floor	One piece aluminium ricegrain
Internal light	3 LED sensor lights
Refrigeration	*Thermo King T-1000R

-20°C*

44.99m³



Rear doors

Thermal efficiency 'K' VALUE .55 W/m²K tested to Australian Standard AS4982

Standard Inclusions

- High density polyurethane insulation •
- European design
- European construction
- Low tare weight
- Higher legal payload Galvanised sub frame
- Recessed stainless door hardware
- Stainless door frames

80mm

- Anodised corner mouldings
- Long life EPDM rubber seals
- Internal LED sensor lights
- Rubber bump stops

- Model No: A7800P-BEHI
 - Rear/side grab handles Recessed load restraint track
 - Moulded plastic mudguards

 - Alloy kick panel
 - Options available to suit customer requirements

