

THERMAXX THE AL	DVANTAGE IS TO YOUR E
BODY DIMENSION External length External width External height	9050mm 2490mm 2650mm
Internal length Internal width Internal height	8820mm 2410mm 2450mm
Pallet loading	14 Pallet capacity
Fitted body weight	*3710kg
PANELS THICKNESS Roof/floor Front wall Side walls	100mm 100mm 40mm

Side door	N/A
Rear door	65mm freezer rated roller door with galvanised frame
Front wall frame	Universal to suit diesel drive units
Side step	N/A
Rear step	Heavy duty crash bar
Cargo track	2 recessed rows @ 800-1400mm 2 shoring bars
Floor	One piece aluminium ricegrain
Internal light	4 LED sensor lights
Refrigeration	*Thermo KingT-1200R

-20°C*

52.08m³



Thermal efficiency 'K' VALUE .64 W/m²K tested to Australian Standard AS4982

Standard Inclusions

European design

Low tare weight

European construction

- High density polyurethane insulation Anodised corner mouldings
 - Long life EPDM rubber seals on roller door •
 - Internal LED sensor lights
 - Rubber bump stops
 - Rear/side grab handles
- Higher legal payload Galvanised sub frame Recessed load restraint track
- Moulded plastic mudguards
- Alloy kick panel
- Heavy duty galvanised rear door frame

Model No: A9050P-EHO

Options available to suit customer requirements

